



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/324,823	06/02/1999	TAKESHI IDE	P99.0654	2056

33448 7590 11/25/2003

ROBERT J. DEPKE LEWIS T. STEADMAN
HOLLAND & KNIGHT LLC
131 SOUTH DEARBORN
30TH FLOOR
CHICAGO, IL 60603

EXAMINER

MOE, AUNG SOE

ART UNIT	PAPER NUMBER
----------	--------------

2612

DATE MAILED: 11/25/2003

15

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary

Application No.

09/324,823

Applicant(s)

IDE ET AL.

Examiner

Aung S. Moe

Art Unit

2612

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
- Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 15 September 2003.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-6 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-6 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. §§ 119 and 120

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some * c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- * See the attached detailed Office action for a list of the certified copies not received.
- 13) ☐ Acknowledgment is made of a claim for domestic priority under 35 U.S.C. § 119(e) (to a provisional application) since a specific reference was included in the first sentence of the specification or in an Application Data Sheet. 37 CFR 1.78.
- a) ☐ The translation of the foreign language provisional application has been received.
- 14) ☐ Acknowledgment is made of a claim for domestic priority under 35 U.S.C. §§ 120 and/or 121 since a specific reference was included in the first sentence of the specification or in an Application Data Sheet. 37 CFR 1.78.

Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☐ Information Disclosure Statement(s) (PTO-1449) Paper No(s) _____
- 4) ☐ Interview Summary (PTO-413) Paper No(s). _____
- 5) ☐ Notice of Informal Patent Application (PTO-152)
- 6) ☐ Other: _____

Art Unit: 2612

DETAILED ACTION

Response to Arguments

1. Applicant's arguments with respect to claims 1-6 have been considered but are moot in view of the new ground(s) of rejection.

Claim Rejections - 35 USC § 103

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

3. Claims 1-2 and 4-5 are rejected under 35 U.S.C. 103(a) as being unpatentable over Yamaguchi et al. (U.S. 6,342,921) in view of Suzuki et al. (U.S. 6,515,703).

Regarding claim 1, Yamaguchi '921 discloses a solid-state image sensor (Figs. 1, 19, 28 and 29) device having an image sensing portion performing photoelectric conversion in both progressive mode in which all picture element signals are output independently (i.e., noted the Frame mode for reading all the pixels in a progressive manner as discussed in col. 1, lines 15+), and interlace mode in which interlaced scanning are performed and the picture element signals obtained in respective scanning in said image sensing portion being superimposed (i.e., noted that during the interlaced mode, one field of image data is reading out as an odd field and an even field, so that such field data are superimposed to display the moving images as discussed in col. 1, lines 25), and the sensor device comprising: a photodiode within the image sensing portion (Fig. 11, the elements 2; col. 11, lines 60-65).

Furthermore, it is noted that although Yamaguchi '921 discloses the CCD device capable of operating at both the progressive mode (i.e., Full frame mode for capturing a still image as discussed in col. 1, lines 20+) and the interlaced mode (i.e., the moving/monitor mode for capturing and displaying a moving image as discussed in col. 1, lines 30+) by applying the respective bias voltage to control the potential of charges stored in the CCD sensor during the different operation mode (i.e., see col. 12, lines 25+, col. 14, lines 5+ and col. 15, lines 5+), Yamaguchi '921 does not explicitly show the use of a substrate-bias generation circuit for applying a basis voltage to the substrate of said image sensing portion and for controlling said bias voltage in said progressive mode (Frame mode) to be smaller than the bias voltage while operating in the interlaced mode (Field mode) as recited in present claimed invention.

Art Unit: 2612

However, the above-mentioned claimed limitations are well known in the art as evidenced by Suzuki '703. In particular, Suzuki '703 discloses that it is conventionally well-known in the art to use a substrate-bias generation circuit for applying a basis voltage (i.e., Fig. 1, the elements' 2, 3 and 4) to the substrate of said image sensing portion (i.e., the CCD sensor of the camera as shown in Fig. 7A-7D of Suzuki '703) and for controlling said bias voltage in said progressive mode (i.e., the Frame mode where the image data are readout as in a non-interlaced manner by applying the respective substrate-bias voltage V_{sub} Level 2 as discussed in col. 2, lines 10+ and col. 12, lines 60+ of Suzuki '703; see Figs. 7A-7D) to be smaller than the bias voltage while operating in the interlaced mode (i.e., noted from the Fig. 7C of Suzuki '703 that the V_{sub} LEVEL2 for the Frame Mode for producing the image data in a non-interlaced manner is less than the V_{sub} LEVEL1 of the Filed mode for producing the interlaced image for displaying the moving image on the EVF 44; see Fig. 7A-7D & 10; and col. 2, lines 1-10, col. 12, line 35+ and col. 13, lines 1+) as recited in present claimed invention.

In view of the above, having the system of Yamaguchi '921 and then given the well-established teaching of Suzuki '703, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the system of Yamaguchi '921 as taught by Suzuki '407, since Suzuki '407 states at col. 19, lines 5+ that such a modification would increase the signal-to-noise ratio in both Full frame reading mode and the Field reading mode so that it is possible to obtain a high-quality image regardless of whether the operation is performed in the field reading mode or in the full frame reading mode.

Regarding claim 4, the combination of Yamaguchi '921 and Suzuki '703 shows wherein the substrate bias generation circuit adjusts the substrate bias voltage during the progressive

Art Unit: 2612

mode of operation such that a potential difference is generated between a doped region (i.e., As shown in Figs. 7B-7C, noted the n-TYPE SUBSTRATE regions of Suzuki '703) and a well of the photodiode (i.e., noted the P-LAYER as shown in Figs. 7B-7C of Suzuki '703) which is greater than during the interlaced operation (i.e., as shown in Figs. 7A-7C, noted the potential difference of the Vsub LEVEL 2 and Vsub LEVEL1 for the respective regions of the image sensor as taught by Suzuki '703).

Regarding claims 2 and 5, it is noted that the method Claims 2 and 5 corresponding to the product claims 1 and 4, thus claims 2 and 5 are rejected for the same reasons as set forth for the claims 1 and 4 as discussed above.

4. Claims 1-3 and 4-6 are rejected under 35 U.S.C. 103(a) as being unpatentable over Chang (U.S. 5,264,939) in view of Suzuki '703 (U.S. 6,515,703).

Regarding claim 1, Chang '939 discloses a solid-state image sensor (Figs. 1 and 2) device having an image sensing portion performing photoelectric conversion in both progressive mode in which all picture element signals are output independently (i.e., noted the Full Frame transfer mode during the non-interlaced reading as discussed in col. 4, lines 40+), and interlace mode in which of interlaced scanning are performed and the picture element signals obtained in respective scanning in said image sensing portion are superimposed (i.e., noted during the interlaced mode, an odd field and an even field are superimposed in an interlaced manner for displaying moving images; see col. 4, lines 6+); and the sensor device comprising: a photodiode (col. 3, lines 40+ and col. 5, lines 55+) within the image sensing portion and applying the

Art Unit: 2612

respective substrate voltages during the operation of different modes (i.e., the interlaced mode and the non-interlaced/progressive mode; see Figs. 2-4).

Furthermore, it is noted that although Chang '939 discloses the CCD device (Fig. 2) capable of operating at both the progressive mode (i.e., Non-interlaced mode for reading the image frame as discussed in col. 4, lines 40+) and the interlaced mode (i.e., the interlaced mode for capturing and displaying a moving image as discussed in col. 4, lines 5+) by applying the respective substrate voltages to the image sensor as shown in Figs. 2 and 3-4, Chang '939 does not explicitly show wherein a basis voltage applied to the substrate of said image sensing portion and for controlling said bias voltage in said progressive mode to be smaller than said voltage in said interlaced mode as recited in present claimed invention.

However, the above-mentioned claimed limitations are well known in the art as evidenced by Suzuki '703. In particular, Suzuki '703 discloses that it is conventionally well-known in the art to use a substrate-bias generation circuit for applying a basis voltage (i.e., Fig. 1, the elements' 2, 3 and 4) to the substrate of said image sensing portion (i.e., the CCD sensor of the camera as shown in Fig. 7A-7D of Suzuki '703) and for controlling said bias voltage in said progressive mode (i.e., the Frame mode where the image data are readout as in a non-interlaced manner by applying the respective substrate-bias voltage $V_{\text{sub Level 2}}$ as discussed in col. 2, lines 10+ and col. 12, lines 60+ of Suzuki '703; see Figs. 7A-7D) to be smaller than the bias voltage while operating in the interlaced mode (i.e., noted from the Fig. 7C of Suzuki '703 that the $V_{\text{sub LEVEL2}}$ for the Frame Mode for producing the image data in a non-interlaced manner is less than the $V_{\text{sub LEVEL1}}$ of the Filed mode for producing the interlaced image for

Art Unit: 2612

displaying the moving image on the EVF 44; see Fig. 7A-7D & 10; and col. 2, lines 1-10, col. 12, line 35+ and col. 13, lines 1+) as recited in present claimed invention.

In view of the above, having the system of Chang '939 and then given the well-established teaching of Suzuki '703, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the system of Chang '939 as taught by Suzuki '407, since Suzuki '407 states at col. 19, lines 5+ that such a modification would increase the signal-to-noise ratio in both Full frame reading mode and the Field reading mode so that it is possible to obtain a high-quality image regardless of whether the operation is performed in the field reading mode or in the full frame reading mode.

Regarding claim 4, the combination of Chang '939 and Suzuki '703 shows wherein the substrate bias generation circuit adjusts the substrate bias voltage during the progressive mode of operation such that a potential difference is generated between a doped region (i.e., As shown in Figs. 7B-7C, noted the n-TYPE SUBSTRATE regions of Suzuki '703) and a well of the photodiode (i.e., noted the P-LAYER as shown in Figs. 7B-7C of Suzuki '703) which is greater than during the interlaced operation (i.e., as shown in Figs. 7A-7C, noted the potential difference of the V_{sub} LEVEL 2 and V_{sub} LEVEL1 for the respective regions of the image sensor as taught by Suzuki '703).

Regarding claim 2, Chang '939 discloses a drive method for a solid-state image sensor device (i.e., Figs. 1 and 3-4) having an image sensing portion including a photodiode (20) within the image sensing portion for performing photoelectric conversion said image sensing portion operation in both progressive mode in which all picture element signals are output independently

Art Unit: 2612

(i.e., noted the Full Frame transfer mode during the non-interlaced reading as discussed in col. 4, lines 40+), and interlaced mode in which pluralities of scanning are performed and picture element signals obtained in respective scanning are superimposed (i.e., noted during the interlaced mode, an odd field and an even field are superimposed in an interlaced manner for displaying moving images; see col. 4, lines 6+).

Furthermore, it is noted that although Chang '939 discloses the CCD device capable of operating at both the progressive mode (i.e., Full frame mode for capturing a still image as discussed in col. 1, lines 20+) and the interlaced mode (i.e., during the interlaced mode, an odd field and an even field is superimposed in an interlaced manner for displaying moving images; see col. 4, lines 6+), and the method including the step of applying the respective voltage to the substrate of the CCD sensor (i.e., see Fig. 2) during the interlaced mode and the non-interlaced mode (i.e., see Figs. 3-4), Chang '939 does not explicitly show wherein in applying a bias voltage to the substrate of said image sensing portion, in said progressive mode the value of said bias voltage is smaller than that in said interlace mode as recited in present claimed invention.

However, the above-mentioned claimed limitations are well known in the art as evidenced by Suzuki '703. In particular, Suzuki '703 discloses that it is conventionally well-known in the art to use a substrate-bias generation circuit for applying a basis voltage (i.e., Fig. 1, the elements' 2, 3 and 4) to the substrate of said image sensing portion (i.e., the CCD sensor of the camera as shown in Fig. 7A-7D of Suzuki '703) and for controlling said bias voltage in said progressive mode (i.e., the Frame mode where the image data are readout as in a non-interlaced manner by applying the respective substrate-bias voltage V_{sub} Level 2 as discussed in col. 2, lines 10+ and col. 12, lines 60+ of Suzuki '703; see Figs. 7A-7D) to be smaller than the bias

Art Unit: 2612

voltage while operating in the interlaced mode (i.e., noted from the Fig. 7C of Suzuki '703 that the Vsub LEVEL2 for the Frame Mode for producing the image data in a non-interlaced manner is less than the Vsub LEVEL1 of the Filed mode for producing the interlaced image for displaying the moving image on the EVF 44; see Fig. 7A-7D & 10; and col. 2, lines 1-10, col. 12, line 35+ and col. 13, lines 1+) as recited in present claimed invention.

In view of the above, having the system of Chang '939 and then given the well-established teaching of Suzuki '703, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the system of Chang '939 as taught by Suzuki '407, since Suzuki '407 states at col. 19, lines 5+ that such a modification would increase the signal-to-noise ratio in both Full frame reading mode and the Field reading mode so that it is possible to obtain a high-quality image regardless of whether the operation is performed in the field reading mode or in the full frame reading mode.

Regarding claim 5, please see the Examiner's comments with respect to claim 4 as discussed above.

Regarding claim 3, Chang '939 discloses a camera (Fig. 1) comprising a solid-state image sensor device (16) having an image sensing portion (Fig. 2) for performing photoelectric conversion (i.e., see Fig. 3, col. 3, lines 40+) and a substrate-bias generation circuit (i.e., Fig. 1, the elements 64, 30, and 32), an optical system (14) receiving incident light from a subject and forming an image on said image sensing portion of said solid-state image sensor device (16), and a signal processing system for processing the signals output from said solid-state image sensor device to obtain a video signal (i.e., see Fig. 1, the elements' 24, 26, 28, and 44-62; noted the use of NTSC standard video signals), wherein the image sensing portion (Fig. 2) includes a

Art Unit: 2612

photodiode structure (i.e., col. 3, lines 40 and col. 5, lines 56), and wherein said driving system selectively operates in (i.e., noted that the imaging system of Chang '939 is capable of operating both in a non-interlaced/Frame mode and the interlace mode for displaying the moving image therein; see col. 3, lines 55+ and col. 4, lines 5+) operate in progressive mode in which all picture element signals are output independently (i.e., noted the Full-Frame/non-interlaced transfer mode as discussed in col. 4, lines 40+), and interlaced mode in which pluralities of scanning are performed (i.e., the scanning for the odd fields and the even fields for producing the interlaced image signals) and the picture element signals obtained in respective scanning are superimposed (i.e., noted during the interlaced mode, an odd field and an even field are superimposed in an interlaced manner for displaying moving images; see col. 4, lines 6+).

Furthermore, it is noted that although Chang '939 discloses the CCD device capable of operating at both the progressive mode (i.e., Full-frame/non-interlaced mode for capturing an image as discussed in col. 4, lines 40+) and the interlaced mode (i.e., the moving/monitor mode for capturing the odd/even fields and displaying a moving image as discussed in col. 4, lines 5+) by applying the respective substrate voltages to the image sensor as shown in Figs. 2-4, Chang '939 does not explicitly show that the bias voltage to be applied to the substrate in said progressive mode being controlled to be smaller than that in said interlaced mode by said substrate-bias generation circuit as recited in the present claimed invention.

However, the above-mentioned claimed limitations are well known in the art as evidenced by Suzuki '703. In particular, Suzuki '703 discloses that it is conventionally well-known in the art to use a substrate-bias generation circuit for applying a basis voltage (i.e., Fig. 1, the elements' 2, 3 and 4) to the substrate of said image sensing portion (i.e., the CCD sensor of

Art Unit: 2612

the camera as shown in Fig. 7A-7D of Suzuki '703) and for controlling said bias voltage in said progressive mode (i.e., the Frame mode where the image data are readout as in a non-interlaced manner by applying the respective substrate-bias voltage V_{sub} Level 2 as discussed in col. 2, lines 10+ and col. 12, lines 60+ of Suzuki '703; see Figs. 7A-7D) to be smaller than the bias voltage while operating in the interlaced mode (i.e., noted from the Fig. 7C of Suzuki '703 that the V_{sub} LEVEL2 for the Frame Mode for producing the image data in a non-interlaced manner is less than the V_{sub} LEVEL1 of the Filed mode for producing the interlaced image for displaying the moving image on the EVF 44; see Fig. 7A-7D & 10; and col. 2, lines 1-10, col. 12, line 35+ and col. 13, lines 1+) as recited in present claimed invention.

In view of the above, having the system of Chang '939 and then given the well-established teaching of Suzuki '703, it would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the system of Chang '939 as taught by Suzuki '407, since Suzuki '407 states at col. 19, lines 5+ that such a modification would increase the signal-to-noise ratio in both Full frame reading mode and the Field reading mode so that it is possible to obtain a high-quality image regardless of whether the operation is performed in the field reading mode or in the full frame reading mode.

Regarding claim 6, the combination of Chang '939 and Suzuki '703 shows wherein the substrate bias generation circuit adjusts the substrate bias voltage during the progressive mode of operation such that a potential difference is generated between a doped region (i.e., As shown in Figs. 7B-7C, noted the n-TYPE SUBSTRATE regions of Suzuki '703) and a well of the photodiode (i.e., noted the P-LAYER as shown in Figs. 7B-7C of Suzuki '703) which is greater than during the interlaced operation (i.e., as shown in Figs. 7A-7C, noted the potential difference

Art Unit: 2612

of the Vsub LEVEL 2 and Vsub LEVEL1 for the respective regions of the image sensor as taught by Suzuki '703).

Conclusion

5. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

a. Burkey '850 and Lee '777 shows a solid-state image sensor having a driving circuit and a substrate-bias voltage generation circuit for providing the bias voltage to the image sensor portion of the camera thereof.

6. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).


A shortened statutory period for reply to this final action is set to expire **THREE MONTHS** from the mailing date of this action. In the event a first reply is filed within **TWO MONTHS** of the mailing date of this final action and the advisory action is not mailed until after the end of the **THREE-MONTH** shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than **SIX MONTHS** from the date of this final action.

Art Unit: 2612

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Aung S. Moe whose telephone number is 703-306-3021. The examiner can normally be reached on Mon-Fri (9-5).

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Wendy Garber can be reached on 703-305-4929. The fax phone number for the organization where this application or proceeding is assigned is (703) 872-9306.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is 703-305-9700.



Aung S. Moe
Primary Examiner
Art Unit 2612

A. Moe
November 20, 2003